
Subject: Sqlld aliasing

Posted by [wqcmaster](#) on Wed, 05 Feb 2014 12:26:41 GMT

[View Forum Message](#) <> [Reply to Message](#)

Similar to this post, we added some kind of Sqlld aliasing.

It works as follows:

database.sch:

```
TABLE__(MyTableName, T1) // Fuer DBDomaenen
  INT__ (MPK) PRIMARY_KEY
  BOOL__ (BooleanVariable, CB1)
  INT__ (NameId, CI1)
  INT__ (VendorId, CI2)
  INT__ (TaskId, CI3)
  STRING__ (Title, CS1, 255)
  STRING__ (Description, CS2, 50)
  TIME__ (Timestamp, CT1)
END_TABLE
```

will now generate the following Sqllds:

```
Sqlld MyTableName("T1");
Sqlld MPK("MPK");
Sqlld BooleanVariable("CB1");
Sqlld NameId("CI1");
Sqlld VendorId("CI2");
Sqlld TaskId("CI3");
Sqlld Title("CS1");
Sqlld Description("CS2");
Sqlld Timestamp("CT1");
```

Well, as you see, aliasing is not the correct terminology, maybe some kind of simple database column name obfuscation.

Patch attached to this post; done against r6693 but also works against r6870.

Something to be included in TRUNK?

File Attachments

1) [sqlldalias.patch](#), downloaded 392 times

Subject: Re: Sqlld aliasing

Posted by [mirek](#) on Mon, 10 Feb 2014 19:05:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

This is interesting idea, but has disadvantage that it needs a fix to all "driver" schema definition headers. I will have to think about it a bit before committing to trunk.
